

Project Scope:

Bid submittal requirement:

1 Hard Copy – 1 Thumb Drive with specs and layout of medial trailer

BASE MODEL:

QSTAB8524+0-2T5.2K – Substitute – Equal or Better

Overall Box Length – 24’-2” – Equal or Better

Overall Box Width (With Awning)– 106 5/16”

Box Width – 100”

Overall Box Height – 10’-6 7/8”

Interior Height – 7’-6”

WARRANTY:

5YR STR, 3 YR LTD, 1 YR ELEC WARRANTY

FRAME:

Axle – 5200# - Torsion – EZ Lube Hubs – Electrical Brakes

Ground Clearance: Raise Approx. 3” From Standard

Axle Spacing – Spread Axle

All Tube Construction

Coupler – A – Frame 2-5/16” – 10,000#

Cross Members – Floor – 16” O/C

Cross Members – Roof – 16” O/C – 1” X 3”

Cross Members – Wall – CS – 16” O/C – 1” X 1.5”

Cross Members – Wall – RS 16” O/C – 1” X 1.5”

Floor Design – Flat

Frame – 5”

Frame – Full Perimeter – Aluminum

Frame Protection – Skid Plates

Frame Protection – Bogey Wheels

Front Design – Flat

Tank – Fuel – Gas – 24 Gallon – End Fill – In Frame

Jack – Tongue – Top Wind – 5000# - Zinc

Jack – Stabilizer – Scissor – 24” – 5000# - Pair

Location: Rear

Tire/Wheel – ST225/75R15/LRE – Radial on Aluminum – W/Stainless Steel Lugnuts

Spare Tire/Wheel – ST225/75R15/LRE – Radial on Aluminum

Includes: Spare Tire Mount – Under Frame – Slideout

Tongue – Extended Triple Tube – 12”

Framing – Bathroom

Overall Trailer Length – 28’-11 3/16”

EXTERIOR:

Awning – 12V With Weather Guard – 21’ – White – Black Fade Vinyl Fabric

Includes: 12V Awning Switch

Weather Guard: Vinyl

Awning Center Support Cradle

Exterior Aluminum – Standard Color

Color: Polar White

Exterior Fastener – Screwless

Exterior Aluminum Thickness - .030

Railing – Viewing Rail – Aluminum – Fold Down

Includes: Bumpers at Corners

Fenderettes – Aluminum

Gravel Guard – ATP – 24” With J Rail

LOGO Program – Mobile County Health Department Branded Graphics Full Body Wrap

Roof – One Piece – Aluminum

Trim – Verticals – Front & Top Radius – Stainless Steel W/ Cast Corners – Polished

Trim – Header – Rear – Color Matched

Trim – Rub Rail – Upper – Aluminum – 4”

Trim – Rub Rail – Lower – Aluminum – 7”

Vent – Roof – 12V

Includes Switch

Battery Not Included

Window – Slider W/ Screen – 36”W X 24”H – Roadside

Window Shade – Day/Night – 38”W X 26”H – White

Window – Slider W/ Screen – 36”W X 24”H – Curbside

Window Shade – Day/Night – 38”W X 26”H – White

Window – Egress W/ Slider and Screen 36”W X 24”H – Roadside

Window Shade – Day/Night – 38”W X 26”H – White

DOORS:

Door – Rear Ramp - Premium – Continuous Aluminum Hinge – 2400# Rated Max Load

- 4000# Vehicle Load

Includes: Transition Flap – TPO – Gray Coin – 58”W X 16”L – Rear Ramp Door

Door – Double – Rear – 76”W X 82”H X 5”D – Commercial Glass

Includes: Recessed Behind Ramp Door

Ramp Door Exterior – Rear – Color Matched

Includes: Railing – Foldable / Stowable

Ramp Door Flooring – Rear – TPO – Gray Coin

Door Latch – Bar Lock – Aluminum

Hasp – Stainless Steel – For Cam Bars/Bar Locks on Ramp Door

Door – Entrance – 405 Series – 32” X 78” – FMVSS Lock

Right Hinge

Gas Shock on Entrance Door

Step – Slide In/Out – Non Slip Grid – Aluminum – 32”

Door Accessories – Add Tinted Window to Entrance Door

Door – Interior – 405 Series – 22” X 78”

Right Hinge

Location: Bathroom to Cargo Area

Door – Fuel – Cast Aluminum - Lockable

INTERIOR:

Interior Height – 7.5’

Partition Wall – Front Section – Inner Front Wall to Wall Partition – 87 7/16”

Partition Wall – Welded Construction – W/ 36” Pocket Door

Partition Wall Covering – Screwless Aluminum – Over Plywood – 3/8”

Cabinet – Aluminum – Upper – Straight – 72”W – W/ Radius Lower Edge – Top Hinged

Doors And Gas Shocks

Cabinet Color: Polar White

Cabinet – Aluminum – Upper – Straight – 36”W – W/ Radius Lower Edge – Top Hinged

Doors And Gas Shocks

Cabinet Color: Polar White

Counter Top – Laminate – Flip Up – Stowable – 140”W X 24”D

Counter Top – Laminate – Fixed – 87.5”W X 20”D

Sofa – Fold Up Sleeper – Stowable – 7’ Black – No Logo

Refrigerator – 4.4 CU. FT. – 120V Only

19.92”W X 32.91”H X 22”D

Includes – Dedicated 15 AMP Receptacle Installed in Base Cabinet

Bathroom Hardware

Interior Ceiling – Screwless Aluminum

Cove Color: Polar White

Ceiling Color: Polar White (Standard)

Spring Box Color: Polar White

Same Material In Bathroom Area

Insulation – Ceiling – Fiberglass Batten – R-11

Interior Walls – Screwless Aluminum – Over Plywood – 3/8”

Wall Color: Polar White (Standard)

Same Material In Bathroom Area

Insulation – Walls – EPS – 1” – R-3

Bubble Foil R-0 Insulation Between Wall Cross Members Where Wiring Present

Flooring – TPO – Gray Coin

Fire Extinguisher – 2.5# BC

Smoke Detector

CO Detector

D-Rings – 5000# - Recessed

Wheel Box – Smooth Aluminum

ELECTRICAL:

Battery – 12V AGM (930 CA, 775CCA)

Used For: Bathroom Package

Battery – 12V AGM (930 CA, 775 CCA)

Isolated To Generator Only

Breaker Box – 50 AMP – 120V Only – 60 AMP Converter – 12V Fuse Panel – Inteli-

Power Unit

Switch – Power Cut-Off – Manual – 12V

Power Inlet – Motorbase – 50A – W/ Shore Cord – 50’

Light – Clearance – LED – 12V – Amber – Lower – (4)

Light – Clearance – LED – 12V – Amber – Upper – (4)

Light – Clearance – LED – 12V – Red – Lower – (2)

Light – Clearance – LED – 12V – Red – Upper – (7)

Light – TailLight – Slimline – LED 12V – Red – (1)

Light – Angled Loading – LED 18” – 12V – Exterior – (1)

Switch – Wall – 12V

Used For: Light – Angled Loading – LED – 18” – 12V Exterior

Light – Scene – LED – High Output – 12V – Non Recessed – 14” X 2.5” Chrome Bezel

- (2)

Switch – Wall – 12V

Used For: Exterior Scene Lights

Receptacle – Interior – 120V – 15A – Total – (8)

GFCI Protected Where Required By Code

Receptacle – Interior – 120V – 20A – Dedicated – (1)

GFCI Protected Where Required By Code

Receptacle – Exterior – 120V – 15A – GFI Protected – (1)

Light – Puck – LED – 2.75” – 12V – Non Recessed – (6)

Switch – Wall – 12V

Used For: Light – Puck – 2.75” – 12V – Non Recessed

Light – Rectangular – LED – 14” – 12V – Surface Mount – (7)

Switch – Wall – 3 Way – 12V

Used For: Light – Rectangular – Led – 14” – 12V – Surface Mount

Switch – Relay – 12V – 30A

Light – Rectangular – LED – 14” – 12V – Surface Mount – (4)

Switch – Wall – Dimmer – 12V

Used For: Light – Rectangular – LED – 14” – 12V – Surface Mount

Light – Dome – LED – 12V – Non Recessed – (1)

Location – Bathroom

Switch – Wall – 12V

Used For: Bathroom Light

Generator – Commercial – 7.0 KW ONAN – GAS – (120V / 240V)

Remote Start

Fuel Gauge

Includes: 1 – For Generator

Generator Compartment – Tongue Mounted – ATP

Expanded Metal on Floor of Compartment Includes 405 Series Double Doors –

Vented Galvanized Liner For Front Wall of Trailer Only Gen Box & Doors Built

To Fit Specific Size of Generator

Transfer Switch – Auto – 50A

Microwave – 0.9 CU. FT. 900W – Oven

Includes: 20A Receptacle – Dedicated – 120V

ELECTRONICS

TV Antenna Prep

Omnidirectional Digital Roof Mount Antenna

12V Input Switch

Exterior Coax Cable Inlet

16” X 14” Wall Backer Plate For TV Mount

Includes: 120V Receptacle

PLUMBING & LP

Sink – Single Bowl – Oval – Stainless Steel – 13.25” X 10.5” X 5” – W/ Faucet

Plumbing – Three Season – Heaters – (3) Tank And Line System

Includes: Lighted Rocker Switches

Toilet – RV Style

Sewer Hose And Holder – 10’

Water – City and Gravity Fill

Water Pump – 3.0 GPM – 12V W/ Winterizing Tap

Tank – Water – Fresh – 48 Gallon

Tank Size May Vary Based on Location of Tanks

Tank – Water – Grey – 45 Gallon

Tank Size May Vary Based on Location of Tanks

Tank – Water – Black – 45 Gallon

Tank Size May Vary Based on Location of Tanks

Monitor Panel – 3 Tank, Battery, Water, Water Pump Switch – White

HEATING & AIR CONDITIONING

Heater – Wall Mount – 120V – 1500W – 5120 BTU – Electric – Chrome Grill

Optional Addons:

Hot Water Heater Tank – Electric – Inside Mounted

ADA Compliant Wheelchair Lift – Undercarriage Mounted – Mechanically Operated

ADA Complaint – All Exterior/Interior Doors – Bathroom – to Meet ADA Compliant
Standards